



TECHNICAL INFORMATION

content:

DISK - map

2

DISK - lights

3

4

5

6

DISK - sound

7

8

9

DISK - horizontal projection + flybars

10

DISK - horizontal projection + trapdoor

11

DISK - section

12

DISK Theatre, Karlova 26, 116 65 Praha 1,

tel./fax: +420 234 244 253, tel./zázn.: +420 234 244 252,

www.divadlodisk.cz, e-mail: disk@divadlodisk.cz


Academy of Performing Arts in Prague, Drama Faculty

-
- auditorium capacity is 90 to 150 (depending on stage lay-out)
 - stage and auditorium lay-out is variable providing possibility to perform in any direction or in a quasi arena configuration
 - 15 electrical flies are available
 - dark blue walls of the theatre can be covered by black velvet curtain resizing the stage to 9 x 9 x 9 meters
 - trapdoor (max 4 x 2 meters) is situated in the middle of the stage
-

Further information:

Email: bohunovsky@divadlodisk.cz, disk@divadlodisk.cz

Tel.: +420 234 244 253





How to get to DISK:


by tram – stops: Karlovy lázně (no. 17, 18), Staroměstská (no. 17, 18), Národní třída (no. 6, 9, 18, 22, 23), Národní divadlo (no. 6, 9, 17, 18, 22, 23)

by underground – Staroměstská (line A), Národní třída (line B)


by bus – Staroměstská (no. 133)



PC FHR 1000W 15x




PC FHR 1000W 4x




SL Strand 15°-32° 14x




SL Strand 50° 5x



ETC Source Four Zoom 2x



Robert Juliat Cricket 1x (on the stand in the control room)



ETC Revolution 10x (2x on the 1. bridge with shapers; others with Iris moduls)
Rigged on the bottom of the catwalks



X - X connection socket panel on the walls of the stage

OPERATING DEVICES**Lighting Console Strand 550:**

- 54 submasters, 999 effects, 999 cues, 500 circuits, programmable
- DMX output
- Remote control through iPAQ pocket PC, WiFi connected
- located in control station – elevated, open balcony

Mobile Lighting Console Jands 500:

- 8 submasters, 9999 effects + bank of implicit effects, 10000 cues, bank of device drivers for most MH (moving heads), upgradeable mainly for MH, but usable for linear reflectors
- DMX output

Mobile Lighting Console Strand MX:

- 24 submasters, 500 cues, 100 effects, programmable
- DMX output

Stable Dimming Units:

- 96 circuits, 5kW each
- DMX controlled
- outputs on catwalks and in walls around stage

Mobile Dimming Units:

- 3 x RAC – 24 circuits, 2kW each
- DMX controlled

LIST OF SPOTLIGHTS

<i>type</i>	<i>number</i>	<i>place</i>
PC (FHR) 1000W	22x	bridges and ceiling
PC (FHR) 1000W	11x	additional
Profil SL / Profile SL 600W 15°-32°	15x	bridges and ceiling
Profil SL / Profile SL 600W 45°	6x	bridges and ceiling
Profil ETC / Profile ETC	2x	front bridge
Sledovací reflektor / Followspot Robert Juliat 1000W	1x	control room
PAR 64 dlouhý / long 1000W	6x	additional
PAR 56 krátký / short 500W	4x	additional
Vana asymetrická / Asymetric floodlight 1000W	6x	additional
Vana symetrická / Symetrical floodlight 1000W	4x	additional
ETC Source Four Revolution (ML)	8x	under the ceiling
ETC Source Four Revolution (ML) + with shapers	2x	front bridge
Stroboskop / Stroboscope Hungaroflash EU DMX 2500W	2x	additional
Mlha / Hazer HazeBase	1x	additional

DIMMERS

96 dimmer circuits max. 2,3 kW
 + 2x RACK 24x dimmers max. 2 kW

LIGHTING CONSOLES

Control room:

Strandlighting 550i
 – 54 submasters
 – 999 effects
 – 999 cues
 – 250 channels
 – 200 fixtures
 remote control: iPAQ pocket PC Wi-fi

Additional lighting console:

Flying pig Jands 500
 – 8 submasters
 – 9 999 effects
 – 10 000 cues
 – library of fixtures

Other DMX equipment:

1x MA lighting merger – I/O: 2/1
 1x MA lighting splitter – I/O: 1/8

There are many possibilities of wiring the system. The most usual configuration is 5.1 settings with an individual LFE management and added cluster (dark green) for microphones and wirelles. For specific configuration and settings please contact disk@divadlodisk.cz for consultation.

The plan displays FRONT L+R (blue, different distances are unified by delay), CENTER (green), BACK SURROUND L+R (brown), SUBBASS (pink)

PA

– DBX DriveRack 480 (more)

Portable:

– DBX DriveRack DD-PA

SPEAKERS:

MAIN:

3 x 2 x JBL MP412 (350W)

2 x JBL MP418S (600W – sub bass)

EFFECTS:

8 x JBL MP410 (300W)

PORTABLE:

4 x JBL MP412 (350W)

AMPLIFIERS:

CROWN 2 x CE2000 (2 x 400W)

CROWN 2 x CE4000 (2 x 600W)

CROWN 4 x XS4300 (2 x 200W)

Portable:

– CROWN 2 x XLS602 (2 x 380W) (more)

MIX

Main (digital) mixing console:

– TASCAM DM-3200 (more) possibilities of surround production – up to 6.1

Portable (analog) mixing console:

– Allen Heat WZ 1442/2+ (10 Mic/Line/Ins/+48V,2+2 Stereo, 4 Groups, 6 AUX (4 + 2 Pre/Post), EQ: HF, HMF, LMF, LF, 100Hz) (more)

– Allen Heat PA12-CP (8 Mic/Line/Ins/+48V,2 Stereo, 2 Buss, 2 AUX (AUX + FX), EQ: HF, HMF, LMF, LF, 100Hz , internal digital effect, amplifier 2x500W)

ADDITIONAL EQUIPMENT

- Lexicon MX 400
- Lexicon MPX 550
- 2 x 2 Feedback reducer DBX AFS 224
- DBX iEQ-15
- Compressor/Limiter/Gate DBX 166XL
- 1 x CD/CF-recorder TASCAM SS-CDR1
- 1 x CD-recorder HHB CDR-850
- 1 x CD-player TASCAM CD-01UPro
- 2 x CD-player TASCAM 450
- 2 x MD-player TASCAM 350
- 1 x DVD-player TASCAM DV-D01

Wireless microphone

- 8 x SENNHEISER EW300 G2 (6x microphone MKE2/BG, 3x handheld transmitter SKM 365, 2x headset DPA 4088-F34)
- 3 x SENNHEISER EM 1031 (microphone MKE2)
- 4 x SENNHEISER EM 1031 (handheld transmitter)


Microphone

Dynamic:

- SENNHEISER e602
- SENNHEISER e604
- SENNHEISER e608
- SENNHEISER e609
- 2 x SENNHEISER e845

Condenser:


- AKG C 414 B-XL II/ST
- AKG Perception 220
- 2x AKG C 451
- 2x SENNHEISER e614



- access point 230V
- access point speakers
- access point mic/line

hrací plocha 9x9m
 bez samet. výkrytů 11x10m
 7 elektrických hrádelových tahů
 8 elektrických hodových tahů
 max. výška kuzisy pod lávkou 4m
 počet sedadel v hledišti 100 - 100mís

1-8 TAHY BODOVÉ (100kg)



12 DISK - section

